

Safety data sheet
according to 1907/2006/EC, Article 31






Printing date 30.11.2010

Revision: 30.11.2010

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** DINITROL PUR 550 MULTIRIMER
- **Relevant identified uses of the substance or mixture and uses advised against**
- **Application of the substance / the preparation** Priming
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
EFTEC AG, Hofstrasse 31, CH-8590 Romanshorn, Switzerland
DINOL GmbH, Pyrmonterstr. 76, D-32676 Lügde
- **Further information obtainable from:**
Tel. +49(0)5281 98298 0, FAX +49(0)5281 98298 60
thomas.suerig@dinol.com
- **Emergency telephone number:** Giftnotruf Berlin +49(0)30 30686 790 Beratung in Deutsch und Englisch.

2 Hazards identification

- **Classification of the substance or mixture**
 - **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**
 -  **Xn; Sensitising**
 R42/43: May cause sensitisation by inhalation and skin contact.
 -  **Xi; Irritant**
 R36: Irritating to eyes.
 -  **F; Highly flammable**
 R11: Highly flammable.
 R52/53-67: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Vapours may cause drowsiness and dizziness.
 - **Information concerning particular hazards for human and environment:**
The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
Has a narcotizing effect.
 - **Classification system:**
The classification is according to the latest editions of the EU-lists, and extended by company and literature data.
-
- **Label elements**
 - **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
 - **Code letter and hazard designation of product:**
- 


Xn Harmful
F Highly flammable
- **Hazard-determining components of labelling:**
Aliphatisches Polyisocyanat
Adduct of an aliph. Polyisocyanate and a Silane

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 30.11.2010

Revision: 30.11.2010

Trade name: DINITROL PUR 550 MULTIRIMER

(Contd. of page 1)

diphenylmethanediisocyanate, isomeres and homologues
· Risk phrases:

- 11 Highly flammable.
 36 Irritating to eyes.
 42/43 May cause sensitisation by inhalation and skin contact.
 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 67 Vapours may cause drowsiness and dizziness.

· Safety phrases:

- 9 Keep container in a well-ventilated place.
 23 Do not breathe aerosol.
 24/25 Avoid contact with skin and eyes.
 37 Wear suitable gloves.
 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
 61 Avoid release to the environment. Refer to special instructions/safety data sheets.

· Special labelling of certain preparations:

Contains isocyanates. See information supplied by the manufacturer

· Other hazards
· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
 · **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 78-93-3 EINECS: 201-159-0	butanone ☒ Xi R36; ☒ F R11 R66-67	50-100%
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate ☒ Xi R36 R10	5-10%
CAS: 28182-81-2	Aliphatisches Polyisocyanat ☒ Xi R43 R52/53	5-10%
CAS: 9016-87-9	diphenylmethanediisocyanate, isomeres and homologues ☒ Xn R20; ☒ Xn R42/43; ☒ Xi R36/37/38	1-5%
	Adduct of an aliph. Polyisocyanate and a Silane ☒ Xn R20; ☒ Xi R43 R10	1-5%
CAS: 77-58-7 EINECS: 201-039-8	dibutyltin dilaurate ☒ Xn R22-48-68; ☒ Xi R36/38; ☒ N R50/53	0.1-1%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

· Description of first aid measures
· After inhalation:

Supply fresh air and to be sure call for a doctor.
 In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.11.2010

Revision: 30.11.2010

Trade name: DINITROL PUR 550 MULTIRIMER

(Contd. of page 2)

- **After swallowing:** Seek immediate medical advice.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Firefighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**
Water
Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
No special measures required.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Maximum storage temperature:** < 35°C
- **Minimum storage temperature:** > 0°C

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.11.2010

Revision: 30.11.2010

Trade name: **DINITROL PUR 550 MULTIRIMER**

(Contd. of page 3)

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.· **Control parameters**· **Ingredients with limit values that require monitoring at the workplace:****78-93-3 butanone**

WEL	Short-term value: 899 mg/m ³ , 300 ppm
	Long-term value: 600 mg/m ³ , 200 ppm
Sk	

108-65-6 2-methoxy-1-methylethyl acetate

WEL	Short-term value: 548 mg/m ³ , 100 ppm
	Long-term value: 274 mg/m ³ , 50 ppm
Sk	

9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

WEL	Short-term value: 0.07 mg/m ³
	Long-term value: 0.02 mg/m ³
Sen; as -NCO	

· **Additional information:** The lists valid during the making were used as basis.· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Respiratory protection:** Not necessary if room is well-ventilated.· **Protection of hands:**

Protective gloves

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

GB

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.11.2010

Revision: 30.11.2010

Trade name: DINITROL PUR 550 MULTIRIMER

(Contd. of page 4)

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

· Form:	Liquid
· Colour:	Black
· Odour:	Characteristic
· Odour threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

· Melting point/Melting range:	Undetermined.
· Boiling point/Boiling range:	76°C

· **Flash point:** -4°C

· **Ignition temperature:** 300°C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

· Lower:	1.8 Vol %
· Upper:	11.5 Vol %

· **Vapour pressure at 20°C:** 105 hPa

· Density at 20°C:	0.96 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.

· **Solubility in / Miscibility with water:** Not miscible or difficult to mix.

· **Segregation coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

· **Dynamic:** Not determined.

· **Kinematic:** Not determined.

· **Solvent content:**

· **Organic solvents:** 65.0 %

· **Solids content:** 31.5 %

· **Other information** No further relevant information available.

10 Stability and reactivity

· **Reactivity**

· **Chemical stability**

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Possibility of hazardous reactions** No dangerous reactions known.

· **Conditions to avoid** No further relevant information available.

· **Incompatible materials:** No further relevant information available.

· **Hazardous decomposition products:** No dangerous decomposition products known.

GB

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.11.2010

Revision: 30.11.2010

Trade name: DINITROL PUR 550 MULTIRIMER

(Contd. of page 5)

11 Toxicological information· **Information on toxicological effects**· **Acute toxicity:**· **LD/LC50 values relevant for classification:**

77-58-7 dibutyltin dilaurate

Oral LD50 175 mg/kg (rat)

· **Primary irritant effect:**· **on the skin:** No irritant effect.· **on the eye:** Irritating effect.· **Sensitization:**

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

· **Sensitisation** May cause sensitisation by inhalation and skin contact.**12 Ecological information**· **Toxicity**· **Aquatic toxicity:** No further relevant information available.· **Persistence and degradability** No further relevant information available.· **Behaviour in environmental systems:**· **Bioaccumulative potential** No further relevant information available.· **Mobility in soil** No further relevant information available.· **Ecotoxicological effects:**· **Remark:** Harmful to fish· **Additional ecological information:**· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **Other adverse effects** No further relevant information available.**13 Disposal considerations**· **Waste treatment methods**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 04 00	wastes from MFSU of adhesives and sealants (including waterproofing products)
08 04 09*	waste adhesives and sealants containing organic solvents or other dangerous substances

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.11.2010

Revision: 30.11.2010

Trade name: DINITROL PUR 550 MULTIRIMER

(Contd. of page 6)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID (cross-border)



- **ADR/RID class:** 3 (F1) Flammable liquids.
- **Danger code (Kemler):** 33
- **UN-Number:** 1866
- **Packaging group:** II
- **Hazard label** 3
- **UN proper shipping name:** 1866 RESIN SOLUTION (vapor pressure at 50°C at most 110 kPa)
- **Tunnel restriction code** D/E

· Maritime transport IMDG:



- **IMDG Class:** 3
- **UN Number:** 1866
- **Label** 3
- **Packaging group:** II
- **EMS Number:** F-E,S-E
- **Marine pollutant:** No
- **Proper shipping name:** RESIN SOLUTION

· Air transport ICAO-TI and IATA-DGR:



- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1866
- **Label** 3
- **Packaging group:** II
- **Proper shipping name:** RESIN SOLUTION

- **Special precautions for user** Warning: Flammable liquids.
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

(Contd. on page 8)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 30.11.2010

Revision: 30.11.2010

Trade name: DINITROL PUR 550 MULTIRIMER

(Contd. of page 7)

· **Technical instructions (air):**

Class	Share in %
I	1-5
NK	50-100

· **EU-VOC:** 66.87 %

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- R10 Flammable.
- R11 Highly flammable.
- R20 Harmful by inhalation.
- R22 Harmful if swallowed.
- R36 Irritating to eyes.
- R36/37/38 Irritating to eyes, respiratory system and skin.
- R36/38 Irritating to eyes and skin.
- R42/43 May cause sensitisation by inhalation and skin contact.
- R43 May cause sensitisation by skin contact.
- R48 Danger of serious damage to health by prolonged exposure.
- R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.
- R68 Possible risk of irreversible effects.

· **Department issuing MSDS:** Entwicklung

· **Contact:** Dr. T.Suerig

· *** Data compared to the previous version altered.**

GB